



WLE WASTE OIL BOILER




FEATURES

- Hot water or steam.
- Optional tankless coils for warm car wash or domestic hot water supply.
- Large rear access for cleaning.
- Two large cleanout doors for fireside cleaning.
- Attractive insulated steel jacket.
- Hinged burner door for easy access to fire chamber.
- Choice of burner/nozzle combinations to satisfy your requirements.
- 2-inch poured refractory floor.
- Water leg design.

MEETS EPA GUIDELINES FOR ON-SITE RECYCLING OF USED OIL.



RECYCLE YOUR USED CRANKCASE OIL, TRANSMISSION FLUID, HYDRAULIC FLUID, SYNTHETIC OILS, ALSO BURNS #1 & #2 FUEL OIL AND BIODIESEL.



Burner swing door and large cleanout doors allow quick and convenient maintenance of combustion area.

At the heart of all our waste oil boilers is the patented Shenandoah burner with its easy-to-clean patented slide-out gun assembly and quick-disconnect. This industry-recognized and time-proven burner incorporates the latest flame control technology and high-voltage multi-try ignition.



AN ECONOMICAL HOT WATER OR STEAM HEATING SYSTEM FOR...

- AUTO DEALERSHIPS
- TRUCKING COMPANIES
- TRUCK AND AUTO REPAIR FACILITIES
- BIODIESEL PRODUCTION PLANTS
- TRANSMISSION REPAIR FACILITIES
- FLOOR OR RADIANT HEAT APPLICATIONS
- HEATING LARGE PROCESS TANKS
- TRUCK AND CAR WASH FACILITIES
- GREENHOUSES
- UNIVERSITIES AND CAFETERIAS

MODELS

350/60 500/60 650*/60 800*/60

	Boilers/Commercial Water Heaters				STANDARD EQUIPMENT: <ul style="list-style-type: none">• ASME Boiler• ASME Relief Valve• Waste Oil Burner w/Primary Control• Waste Oil Pump and Filter Kit• Installation Kit & Manual• Insulated Flush Jacket• Theraltimeter Gauge• Operating and Manual High-Limit Aquastats or Pressure Controls• Low Water Cut-Off• Cleanout Brush OPTIONAL EQUIPMENT: <ul style="list-style-type: none">• Oil Storage Tanks• Hydronic Unit Heaters• Hydronic Duct Coils
Waste Oil GPH (approx.)	2.5	3.5	4.6	5.7	
Input BTUH (approx.)	350,000	500,000	650,000	800,000	
Gross Output BTUH (approx.)	280,000	400,000	520,000	640,000	
Gross H.P.	8	12	16	19	
Combustion Volume, Cu. Ft.	10.5	10.5	10.5	10.5	
Water Volume, Gals.	133	133	133	133	
Boiler Width, without Controls (inches)	31.5	31.5	31.5	31.5	
Depth, w/Burner & Smoke Hood (inches)	68	68	68	68	
Boiler Height (inches)	63.6	63.6	63.6	63.6	
Flue Outlet (inches)	10	10	10	10	
Burner	WO-B5	WO-B10	WO-B10	WO-B10	
Boiler Weight (Dry)	1,700 lbs.	1,730 lbs.	1,730 lbs.	1,730 lbs.	
Total Shipping Weight (approx.)	2,450	2,475	2,475	2,475	
Potable Water Output @ 100°F rise, gallons/hr.	336**	470**	636**	750**	
Compressed air Requirements @ 40 psi	2 CFM	4 CFM	4 CFM	4 CFM	
Electrical Requirements (all models)	115/60 15 Amp (220/50 7.5 AMP also available) Water circulator not included				
Fuels: Used crankcase oil, transmission and hydraulic fluids, synthetic oils, and other petroleum based lubricants (any weight combination up to SAE 50 including #1 and #2 fuel oil)					
Agency listings (all models)	ETLM (per UL 796, UL 296A, NFPA 31, 70 and 211), ASME stamped				
Canadian Boiler Registration	Nationally Registered for sale and use in Canada, CRN: K0781.1				
Operating Pressure	15 psi Steam, 30 psi Water				

*Units over 500,000 BTU may require permit for installation

**Water coils are an option on these models, and must be ordered separately



Manufactured in the USA by
Pottstown Engineered Products, Inc.

Local Distributors:
Northwest Industrial Equipment, Inc.
(253) 872-6060
www.OilBurners.com



DAS 2734
7/24